


ZBAMB2011T
Deactivator Antenna,
Countertop



ZBAMB2011F
Deactivator Antenna,
Flushmount

Value Pad Deactivator

The Sensormatic Value Pad Deactivator deactivates active AM EAS labels up to four inches above the surface of the pad for a reliable and virtually seamless process while expediting throughput at the point-of-sale (POS). This unit uses a two-step detect and deactivate process. The integrated status indicators provide visual and audible notifications when live labels are successfully detected and deactivated.

In addition, the deactivator acts as a double-checking device if an associate is ever uncertain whether the label was deactivated. The integrated keypad allows associates to control the volume and tone of the deactivator to distinguish it from other POS equipment. The keypad also initiates the "power-save" mode to help prevent theft by turning the unit off.

With a variety of installation options available – countertop, vertical and flush mount – the sleek design and small footprint maximizes POS counter space. The Value Pad operates off an ordinary electrical outlet and does not require a separate controller.

When connected to a compatible EAS data management device, real-time deactivation counts can be generated into user-friendly customizable reports to provide business-critical data.

Retailer Values

- // Scan-enable functionality only deactivates labels with a valid barcode
- // Slim design allows maximum use of POS space
- // EAS connectivity option allows for generation of operational information to help quickly identify and correct performance
- // Built-in audible and visual indicators provide immediate feedback when active labels are detected and deactivated

Product Codes

ZBAMB2011T
Deactivator Antenna, Countertop Mounting Hardware, Power Cord

ZBAMB2011F
Deactivator Antenna, Flushmount Bracket, Power Cord

ZBAMB2011
Deactivator Antenna

5606-0079-01
Power Supply

ZBAMB1101
Deactivator Antenna (without keypad)

Product Compatibility

- All Sensormatic AM EAS Labels
- Local Device Manager II (LDM II)
- Remote Alarm Module

Specifications

- Length** 21cm (8.3in)
- Width** 16cm (6.3in)
- Height** 4cm (1.6in)
- Weight** 0.95kg (2.1lbs)
- Power Cord Length** 170cm (5.5ft)
- Power Supply Weight** 0.28kg (0.6lbs)

Electrical

Deactivator

Input Voltage 18Vdc, 1.7A

Separate Power Supply

Input Voltage 100–240Vac, 50/60Hz
 AC Line Current 1Arms (max.)
 Output Voltage 18Vdc,
 1.7A Listed Class 2

Certified Limited Power Source

Environmental Constraints

Operating Temperature

0°C to 35°C (32°F to 95°F)

Enclosure

0 to 90%, non-condensing

Declarations**EMC**

47 CFR Part 15
RSS 210
EN 300330
EN 301489

Safety (second edition)

UL 60950-1
CSA C22.2.60950-1
EN 60950-1

EMF

EN 50364

CE This product is in conformity with
RoHS II Directive 2011/65/EU and REACH
Substances of Very High Concern as
defined in Regulation (EC) No 1907/2006
and subsequent amendments to both.