Maverick PT-6410



Features

- All-in-one panel PC style with 15" touch display
- Power efficient
- Intel® Celeron J1900 QC 2.0Ghz
- Fanless system with aluminum enclosure design
- IP64 water and dust proof protection for front panel
- Stylish and rimless flat panel design with VESA mount supporting
- Optional built-in VFD or 8" / 15" customer display
- 5V/12V DC powered COM with jumper-less BIOS setting
- Easy installation and maintenance for HDD and CF / CFast card slot
- Optional 1D/2D barcode scanner, MSR, smart card, Mifare RFID, iButton or fingerprint reader devices
- Optional UPS battery backup



Specifications

Model	PT-6410
Display	
LCD Display Size	TFT LCD 1024x768
Max. Resolution	350 cd/m 16.2M/
Brightness	262K colors LED
Touch Panel	
	Five-Wire Analog Resistive or Projected
Type	Capacitive
Processor	
CPU/ Chipset	Intel® Celeron J1900 QC 2.0Ghz
Memory	One SO-DIMM socket supports DDR3L
	1333 up to 8GB
Storage	2 CFast x 1
	22.5" SATAII HDD x 1
	X 3 (USB 2.0)
USB	X 1 (USB 3.0)
PS/2	X 1 (for Keyboard)
	X 3 (D-type 9 pins powered COM with DC 5V/
Powered COM	12V selection)
1/0	
COM	X 1 (RJ45 CONN)
Connectors	
Cash Drawer Port	X 1 (12V RJ11 cash drawer port)
Line-out	X1
Audio Port Mic-in	X 1
Speaker	X 1
VGA	X 1
Parallel	X 1 (optional, alternative to COM3)
Network	
LAN	X 1 (RJ45 10/100/1000 Base-T)
Option	VFD/ Second display/ MSR/ iButton/ Fingerprint
	reader/ Smart card reader/ MIFARE RFID/ 2D
	Barcode scanner
Enviroment	
Temperature	
Operation	32° to 95° F (0° to 35° C)
Storage	-4° to 140° F (-20° to 60° C)
Relative Humidity	20% to 80% non-condensing
Power Supply	90W or 120W (option with second display)
	power adapter
OS Support	WS7E / POSReady 7 / Windows
The state of the s	Embedded 8.1 Industry
Chassis Housing	Aluminum
Dimension	323.6(W) x 264.2(H) x 368(D) mm

[•] Note: all features and specifications are subject to change without notice. all information subject to mistakes and alteration.

