

iMaverick PT-7500(i3)



Features

- All-in-one panel PC style with 15" touch display
- IP64 water and dust proof protection for front panel
- Stylish and rimless flat panel design with VESA mount supporting
- Optional built-in VFD or 8" / 15" customer display
- 5V/12V DC powered COM with jumper-less BIOS setting
- Easy installation and maintenance for HDD and CF / CFast card slot
- Optional 1D/2D barcode scanner, MSR, smart card, Mifare RFID, iButton or fingerprint reader devices



Retail In Operation

Specifications

Model	PT-7500 (i3)
Display	
LCD Display Size	TFT LCD 1024x768
Max. Resolution	350 cd/m 16.2M/
Brightness	262K colors LED
Touch Panel	
Type	Five-Wire Analog Resistive or Projected Capacitive
Processor	
CPU/ Chipset	Intel® Core™ I3-4330TE 2.4GHz
Memory	One SO-DIMM socket supports DDR3 1600 up to 8GB
Storage	CFast x 1 2.5" SATAIII HDD x 1
USB	X 2 (USB 2.0) X 2 (USB 3.0)
PS/2	X 1 (for Keyboard)
Powered COM	X 2 (D-type 9 pins powered COM with DC 5V/ 12V selection)
I/O	
COM	X 1 (RJ45 CONN)
Connectors	
Cash Drawer Port	X 1 (12V RJ11 cash drawer port)
Line-out	X 1
Audio Port Mic-in	X 1
Speaker	X 1
VGA	X 1
Parallel	X 1 (optional)
Network	
LAN	X 1 (RJ45 10/100/1000 Base-T)
Option	VFD/ Second display/ MSR/ iButton/ Fingerprint reader/ Smart card reader/ MIFARE RFID/ 2D Barcode scanner
Enviroment	
Temperature	
Operation	32° to 95° F (0° to 35° C)
Storage	-4° to 140° F (-20° to 60° C)
Relative Humidity	20% to 80% non-condensing
Power Supply	180W power adapter
OS Support	WS7E / POSReady 7 / Windows Embedded 8.1 Industry
Chassis Housing	Aluminum
Dimension	323.6(W) x 264.2(H) x 368(D) mm

• Note: all features and specifications are subject to change without notice.
all information subject to mistakes and alteration.