

XANDER 7

PT5600

Swift, Price Effective
and High Performance POS



- ◆ Refined & easy installation design
- ◆ Convenient Top I/O interface
- ◆ Dual Sided Smart Card(IC Card) Reader
- ◆ Adapted PCAP Multi Touch Screen
- ◆ Easy maintenance



Retail In Operation

Possibilities & Beyond



- ◆ Top I/O Interface
- ◆ Dual Sided IC Card Reader
- ◆ PCAP Multi Touch
- ◆ Easy maintenance



Specification

		XANDER 7
SYSTEM	Processor	Intel® Celeron® J1900 (2M Cache, 2.0 GHz) Intel® Core™ i3-7100U (3M Cache, 2.4 GHz) Intel® Core™ i7-7500U (4M Cache, 2.7 GHz)
	Graphic	Integrated Intel® HD Graphics engine
	Memory	J1900 -- 4GB(up to 8GB) DDR3L or DDR4 SO-DIMM x 1 i3 / i5 - 8GB DDR3L or DDR4 SO-DIMM x 1
	Storage	M.2 SSD / 2.5" SSD or HDD
	OS	Windows 7, Windows 10, POSReady 7, Win10 IoT
	Audio	Realtek ALC662-VD
Display	Type	15" TFT LED Backlight LCD
	Resolution	1024 x 768
	Brightness	250~300 cd/m ² (typ.)
	Touch	Projective Capacitive Touch(Multi 10 Point)
Interface	Display	1 x VGA
	USB	6 (Rear 4, Back 2, USB 2.0 x 5 / 3.0 x 1) 4 internal (Reserved for MSR, SCR, i-Button/Touch Controller)
	Serial Port	4 x RS-232C (4 x RJ-45)
	PS /2	
	LAN	1 x Gigabit Ethernet, RJ-45
	Audio	1 x Line-out
	Cash Drawer Port	1 x CR Port, RJ-11(Optional)
	Power DC-IN	Input100~240V/50~60Hz 1 x (4 Pin Connector)
	Power DC-OUT	12V OUT(2nd Display Power)
	Power Supply	Adaptor 60W(12V/5A), 96W(12V/8A)
Option	CDP	9.7" TFT LCD(1024 x 768), VFD(20 x 2 Lines)
	Card Reader	Magnetic Stripe Reader(MSR) Comply with ISO 7811, Track 1,2,3 IC Card Reader EMV Level 1, 2 i-button Reader(Dallas)

• Note: all features and specifications are subject to change without notice.
all information subject to mistakes and alteration.